

DIFFERENTIAL PRESSURE ACCURACY

0 to 20% of Range: $\pm(0.02\%$ of Full Scale + Static Line Effect*)

20% to 110% of Range: $\pm(0.1\%$ of Reading + Static Line Effect*)

*Static Line Effect: 0.00002 bar/bar lowest static pressure.

Includes all effects of linearity, hysteresis, repeatability, temperature, and stability for one year.

For continuous vacuum use, connect to the right (-) port marked "Vacuum this side."

OPERATING TEMPERATURE

Temperature Range: **-10 to 50° C (14 to 122° F)**

Non-condensing. No change in accuracy over operating temperature range. Gauge must be zeroed to achieve rated specification.

DISPLAY

Screen: **5.5 digits, 16.9 mm (0.67") high**

Display Rate: **4 readings/second (standard)**
8 readings/second (PSV mode)

LCD readable in sunlight with bright backlight.

PSV mode is intended for Pressure Safety Valve testing, and requires software to enable. (ConfigXP is a free download from XP2i.com.)

POWER

3 x AA: **1500 hours, typical**

Ultra Low Power: **> 1 year, typical****

Uses 3 alkaline AA (LR6) batteries. Use of backlight and/or RS232 reduces operating time.

Optional AC power supply available.

WARNING: Do not use AC power supply in hazardous locations.

******20 minute recording interval or greater in LT5 mode.

DATA/COMMUNICATION

Digital Interface: **RS232, DB-9F**

Free Labview® drivers and programming instructions are available for download from website.

WARNING: Do not use RS232 in hazardous locations.

DATALOGGING

Capacity: **32 000 data points**

Storage Type: **Non-volatile flash memory**

Minimum Interval: **1 second**


Maximum Interval: **18 hours**

Min. Event Duration: **250 mS*****

DataLoggerXP Firmware Update may be purchased at time of order, or an Upgrade Package may be purchased afterward.

Software available for download from our website. Compatible with 32 & 64 bit Windows 7, Vista, and XP (32 bit only). Produces csv files, or uses Excel template files (samples included) to automatically format and graph data.

******* Logging Type - Average with Peaks.



ENCLOSURE

Weight: 915 g (2.0 lbs)	<i>Weight includes batteries.</i>
Rating: IP67	<i>Submersible to 1 m for 30 minutes [IEC 60529].</i>
Housing: Diecast aluminum	<i>Nickel plating over low copper, marine grade aluminum.</i>
Keypad and Labels: UV Resistant Polyester	<i>LCD protected from impact damage by 1.5 mm (0.06") thick polycarbonate lens under polyester window.</i>
	<i>Skydrol® compatible.</i>
	<i>U.S. Patent D612277</i>

SENSOR

Wetted Materials: 300 Series stainless steel and buna-n (internal o-ring)	<i>All welded, with a permanently filled diaphragm seal.</i>
Diaphragm Seal Fluid: Dow Corning® 200	<i>Optional connection on back.</i>
Connection: 1/8" Female NPT	
Max. Static Line Pressure: 7 bar	

STORAGE TEMPERATURE

Temperature Range: -40 to 75° C (-40 to 167° F)	<i>Batteries should be removed if stored for more than one month.</i>
--	---

SPECIAL FEATURES

The following requires the use of our free [ConfigXP](#) software

- User Defined Unit: **Allows the user to define and display any pressure units not included, or to use the gauge to display force, level, or other pressure related parameters. Reduce or increase displayed resolution.**
- PSV Mode: **Intended for pressure safety valve / burst disk testing. 8 readings per second. Captures point at which valve opens, as well as reseal pressure.**
- Averaging: **Smooths unsteady readings (1 to 10 samples).**
- Remove: **Unwanted pressure units from Units button.**
- Disable: **Peak pressure button.**
- Limit or Disable: **Zero button.**
- Password Protect: **Changes to configuration or calibration factor(s).**
 - Save: **Configuration to a file.**
 - Copy: **Configuration can be copied to other gauges.**

CERTIFICATIONS



**II 1G Ex ia IIC T4/T3 Ga
FTZU 12 ATEX 0048X**

This product conforms to:

EN 60079-0: 2009 | EN 60079-11: 2012 | EN 60079-26: 2007



**Ex ia IIC T4/T3 Ga
IECEx FTZU 12.0009X**

This product conforms to:

IEC 60079-0: 2011 | IEC 60079-11: 2011-06 | IEC 60079-26: 2006



Intrinsically Safe and Non-incendive for Hazardous Locations: Class I, Division 1, Groups A, B, C and D, Temperature Code T3C or T4/T3C.



XP2i-DP complies with the Electromagnetic Compatibility and the Pressure Equipment Directives. Refer to the EC Declaration of Conformity for specific details.



The instrument was tested against **AS/NZS 3584**, C-tick EMC/EMI requirements.



XP2i-DP is approved for use as a portable test instrument for Marine use and complies with Det Norsjke Veritas' Rules for Classification of Ships, High Speed & Light Craft and Offshore Standards.

RANGE & RESOLUTION TABLE

P/N	Over pressure (+/- ports)	Display Resolution									
		bar	mbar	kPa	MPa	psi	in H ₂ O	in Hg	mm Hg	mm H ₂ O	kg/cm ²
1BAR	6.5x / 3.0x	0.0001	0.1	0.01	0.00001	0.001	0.01	0.001	0.01	1	0.0001
7BAR	2.0x / 2.0x	0.0001	0.1	0.01	0.00001	0.01	0.1	0.01	0.1	1	0.0001

ORDERING INFORMATION

P/N	Model	Connection: Location	Panel Mount?	Data-logging?
_____	XP2i-DP	_____	_____	_____
	Standard:	Bottom: (omit)	No: (omit)	No: (omit)
	Options:	Back: -RP	Yes: -F4	Yes: -DL
		"omit" for -F4 panel mount	Includes -RP option	

SAMPLE PART NUMBERS

1BARXP2i-DP 1 bar differential gauge
 7BARXP2i-DP-DL 7 bar differential gauge, with the DataLoggerXP option

ACCESSORIES



Protective Boot P/N 3696

Protect your XP2i-DP even more from harsh environments with our form fitting chemical resistant thermo-plastic boot (Skydrol fluid compatible).

AC Adapter Kit P/N 2984

For continuous use applications without battery replacement concern. Input voltage: 100 - 240V, 50-60 Hz. Includes all available international plugs. (Not for use in hazardous locations.)

COMPLIMENTARY PRODUCTS

Crystal Engineering offers a wide range of products that work with the XP2i-DP:

- [Fittings that connect without tools, safely and without leaks](#)
- [Lightweight, super flexible high pressure hoses](#)
- [Complete Calibration Kits](#)
- [Pneumatic hand pump](#)
- [Hydraulic hand pump](#)
- [Portable pressure comparators](#)
- [Software, for the quickest way to calibrate pressure transmitters and gauges](#)

Dow Corning is a registered trademark of Dow Corning Corporation.